LUBRIGREASE FOOD GRADE WHITE GREASE
A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Withstands heat to 500°F. Temperatures above 400°F may require periodic reapplication.

FOR USE BY: Bakeries, Bottlers, Breweries, Canneries, Dairies, Egg Processors, Meat and Poultry Processors, Pharmaceutical Manufacturers and Food Processing and Packaging Plants.

DIRECTIONS FOR USE
Pump in new grease until old grease comes out. Remove old grease if possible.
For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO
Inyecte grasa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si es posible.
Para conexiones de tipo bola, llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause eye irritation. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vomito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contacte al médico.

CONTAINS (CAS#): Mineral Oil (8042-47-5), Calcium Sulfonate Complex (N/A).

HMIS Ratings: Health - 0, Flammability - 1, Reactivity - 0, Personal - A.

NLGI GRADE: 2

148LUBRIGRS

Made in USA 600002176



2205 Old Philadelphia Pike
Lancaster, PA 17602
717-392-7550



LUBRIGREASE

Food Grade White Grease Lubricant

- Reduces Friction and Wear
- Resists Extreme Pressure, Corrosion, and Water Washout
- Ideal for Chains, Cables, and Moving Assemblies
- Sets up Fast and Resists Throw Off
- Temperature Range of -40° to 500°F



CAUTION / PRECAUCIÓN:

KEEP OUT OF REACH OF CHILDREN
See Additional Cautions on Back Panel
NO SE DEJE AL ALCANCE DE LOS NIÑOS
Vea Precauciones Adicionales en el Panel Trasero

NET CONTENTS 14.5 OZ. (411 g)